

Technický list produktu (datasheet): DS276010-A

Stojanový rozvaděč 27U š.600mm hl.1000mm RAL 7035 + RAL 5005

Kompletně sestavený, přední skleněné dveře s klikou (bez vložky zámku)



SCHRACK-Info

TECHNICAL DATA

- The frame, the door, the side panels, the roof plate and the base plate are made of 1.0 mm sheet metal. The mounting for the optional castors is made of 2.0 mm sheet metal. All these parts are made of DC01 quality sheet steel. The vertical rails are made of galvanised sheet metal with a thickness of 2.0mm.
- Welded powder-coated sheet steel skeleton
- Height: 27U
- Width: 600mm
- Depth: 1000mm
- Colour:
 - Light Grey RAL7035.
 - frame Blue RAL5005
- Maximum Load:
 - 15-22U: 300kg
 - 27-47U: 400kg
- Degree of protection: IP20
- 4 mm thick safety glass doors with handsome swing handle. Prepared for half-cylinder type locks. Halfcylinder lock (Order-number: DV900333), Depth= 40mm, Diameter= 17mm, Fixing= M5 Screw, optional available.
- Doors hinged right. Can be changed to hinging on left.
- External hinge system allows up to 180 degree door opening angle.

- Glass doors can be replaced by optional DSRT doors (full metal or perforated, full width or double-wing).
- Removeable and lockable side-panels. Key included. For better passive cooling, side-panels can be replaced by optional perforated side-panels DSRS.
- Removeable and lockable rear-panel. Key included. Rear panel can be replaced by optional DSRT doors (glass, full or perforated metal, full width or double-wing) or by perforated rear-panel DSRR.
- 19" rails (4 pcs.) galvanised, continuously depthadjustable. Numbering of Height-Units (U) by laser for easy readability.
- In 800mm wide DS enclosures, you can choose to adjust the 19" rails to a width of 21".
- In 900, 1.000 and 1.200 mm deep DS enclosures, there is an additional pair of vertical rails installed in half depth. This makes installation of high depth accessories together with standard accessories possible at the same time.
- Space between front vertical 19"-rail and door glass at max. spacing:
 - W600 – 35mm
 - W800 – 50mm
- Space between rear vertical 19"-rail and rear panel at max. spacing:
 - W600 – 35mm
 - W800 – 55mm
- Maximum distance between vertical rails (19"-rails) in free-standing cabinets:
 - W600 x D400 – 310mm
 - W600 x D600 – 510mm
 - W600 x D800 – 710mm
 - W600 x D900 – 810mm
 - W600 x D1000 – 910mm
 - W600 x D1200 – 1110mm
 - W800 x D600 – 470mm
 - W800 x D800 – 670mm
 - W800 x D900 – 770mm
 - W800 x D1000 – 870mm
 - W800 x D1200 – 1070mm
- Maximum usable depth in free-standing cabinets when installed e.g. on shelves:
 - D400 – 375mm
 - D600 – 575mm
 - D800 – 775mm
 - D900 – 875mm
 - D1000 – 975mm
 - D1200 – 1175mm
- Spacing between vertical 19"-rails: 451 mm
- Roof construction with opening, 19" punched. Flexible covered by removable plates of different heights to allow installation of fan-units and cable-entry panels. Remaining opening can be closed by use of one these plates.
 - D400 - Opening: 6U, Covering: 1 x 4U and 1 x 2U
 - D600 - Opening: 8U, Covering: 1 x 4U and 2 x 2U
 - D800 - Opening: 10U, Covering: 2 x 4U and 1 x 2U
 - D900 - Opening: 12U, Covering: 2 x 4U and 2 x 2U
 - D1000 - Opening: 12U, Covering: 2 x 4U and 2 x 2U
 - D1200 - Opening: 12U, Covering: 2 x 4U and 2 x 2U
- Floor construction with opening, 19" punched. Covered by removable plate in full height.
 - D400 - Opening: 6U, Covering: 1 x 6U
 - D600 - Opening: 8U, Covering: 1 x 8U
 - D800 - Opening: 10U, Covering: 1 x 10U

- D900 - Opening: 12U, Covering: 1 x 12U
- D1000 - Opening: 12U, Covering: 1 x 12U
- D1200 - Opening: 12U, Covering: 1 x 12U
- Roof unit assemblies can also be fitted to floor section. Optional base required.
- Cable entry possible via roof, floor and rear panel. Delivered with demountable or break-out blanking plates.
- Brush strip panel for roof (DBK24800) optional.
- Air vents for passive ventilation.
- Earthing:
 - M8-Earthing point plus 19"-Earthingset in the rear of the cabinet
 - FastOn-Earthing-connections to all dismountable parts pre-installed
- Included assembly materials:
 - 16 x Cage nuts, bolts and washers M6
 - 4 x Levelling feet
- Wide range of available accessories (bases, fan-units, cable entry panels, fixed shelves, patch panels, cable management, PDUs, doors, etc.).
- Enclosure is delivered fully-assembled on a disposable pallet.

Technické informace

Šířka (netto) (mm)	600,00
Výška (netto) (mm)	1.300,00
Hloubka (netto) (mm)	1.000,00
Hmotnost (netto) (kg)	69,20
Minimální teplota okolí (°C)	0
Maximální teplota okolí (°C)	40
Vhodné pro U	27U-1300 mm
Barva	RAL 7035 / RAL 5005 (světle šedá / modrá)

Tabulka objednacích čísel

POPIS	OBJ. ČÍSLO
Stojanový rozvaděč 27U š.600mm hl.1000mm RAL 7035 + RAL 5005 Kompletně sestavený, přední skleněné dveře s klikou(bez vložky zámku)	DS276010-A
Volitelné příslušenství	
Půlvložka s klíčem 333 včetně 1 ks zápuštného šroubu M5x16 mm z nerezové oceli V2A	DV900333S
Horní/spodní kabelová průchodka s protiprach.kartáčem, 2U	DBK24800
Stropní vent. jednotka, 2x ventilátor, termostat, 4U, šedá RAL7035, pro stojanové rack DS/DSZ a DSS	DLT44802-A
Boční panel (pár) podstavce pro rozvaděč DS,hl. 1000mm	DSOT1210

Tabulka objednacích čísel

POPIS	OBJ. ČÍSLO
Volitelné příslušenství	
Přední/zad.panel podstavce,perf.+protiprachový filtr,š.600mm Ke stojanovým rozvaděčům, barva RAL7035	DSOF1263
19" vyvaz.kovový panel,5x velké kovové oko, 1U, barva šedá	DBC14805
19" vyvaz.panel, 5xvelké tvrdé plastové oko, 1U, barva šedá	DBK14805
19" polička s perf.,hl. 450mm, šroub.,zátěž 80kg, 1U,RAL 7035	DFS14845-C
Napájecí panel PDU 19", 9x SCHUKO, 1U, kabel 3 m	IU070114-3
Napájecí panel PDU 19", 7x SCHUKO, přep.ochrana, 1.25U, 2 m 2m-connector cable, RAL7035	IU070113
19" napájecí panel PDU, 9x Schuko, vypínač, 1U, 2 m, černý Hliníkový profil	Q7070114-A
19" napájecí panel PDU, 7x Schuko, přepěťová ochrana, 1U Přívodní kabel 2 m, černý, hliníková profil	Q7070113-A
Montážní sada M6 (šroub, matice, podložka - sada 50 ks)	DSSRA050
19" montážní deska perforovaná, výška 14U, ocelový plech Včetně šroubů a matic	DMP1914
LED osvětlovací jednotka do 19" nebo magnetická, černá Včetně PIR detektoru na pohyb, externí napájecí zdroj	DTLIGHT01
Switch L2 neřízený 24xRJ45 10/100/1000, 19",interní PSU,tichý 19" provedení, kovové šasi, interní PSU	QLGSW2457
19" patchpanel pro max. 24 keystone,neosazený, 1U,RAL 7035 Dvoudílná konstrukce rámu a vyvazovacího panelu, barva světle šedá	HSER0240GS