


Technický list produktu (datasheet): DSZ458080-

Stojanový rozvaděč rozebíratelný 45U š.800mm hl.800mm

Barva: RAL 7035 + RAL 5005



SCHRACK-Info

- Powder-coated sheet steel skeleton 1,5mm
- Height: 45U
- Width: 800mm
- Depth: 800mm
- Demountable Parts:
 - Front Part: 105mm
 - Rear Part: 105 mm
- Main Part welded:
 - 390mm at 600 deep enclosure
 - 590mm at 800 deep enclosure
 - 690mm at 900 deep enclosure
 - 790mm at 1.000 deep enclosure
 - 990mm at 1.200 deep enclosure
- Colour: Light Grey RAL 7035,
- Frame Blue RAL 5005
- Maximum load:
 - 15 – 22U: 300 kg
 - 27 – 47 U: 400kg

- Degree of protection: IP20
- 4 mm thick safety glass doors with handsome swing handle. Prepared for half-cylinder type locks. Halfcylinder lock (Order-number: DV900333), Depth= 40mm, Diameter= 17mm, Fixing= M5 Screw, optional available.
- Doors hinged right. Can be changed to hinging on left .
- External hinge system allows up to 180 degree door opening angle.
- Front glass door can be replaced by optional DSRT metal door (full metal or perforated).
- Removeable and lockable rear and side panels. Key included.
- Rear panel can be replaced by optional DSRT rear door. Glass- or metal door (full metal or perforated). 19" rails (4 pcs.) galvanised, continuously depthadjustable. Numbering of Height-Units (U) by laser for easy readability.
- In 800mm wide DSZ enclosures, you can choose to adjust the 19" rails to a width of 21" .
- In 900, 1.000 and 1.200 mm deep DSZ enclosures there is an additional pair of vertical rails installed in half depth. This makes installation of high depth accessories together with standard accessories at the same time possible.
- Space between front vertical 19"-rail and door glass at max. spacing:
 - W600 – 43mm
 - W800 – 50mm
- Space between rear vertical 19"-rail and rear panel at max. spacing:
 - W600 – 45mm
 - W800 – 55mm
- Maximum distance between vertical rails (19"-rails) in free-standing cabinets:
 - W600 x D600 – 494mm
 - W600 x D800 – 694mm
 - W600 x D900 – 794mm
 - W600 x D1000 – 894mm
 - W600 x D1200 – 1.094mm
 - W800 x D600 – 470mm
 - W800 x D800 – 670mm
 - W800 x D900 – 770mm
 - W800 x D1000 – 870mm
 - W800 x D1200 – 1.070mm
- Maximum usable depth in free-standing cabinets when installed e.g. on shelves:
 - D600 – 575mm
 - D800 – 775mm
 - D900 – 875mm
 - D1000 – 975mm
 - D1200 – 1.175mm
- Spacing between vertical 19"-rails: 451 mm
- Roof construction with 19" punching.
- 600 mm deep DSZ enclosures come with 8U deep roof aperture, flexible covering with 1 x 4U and 2 x 2U cover plates.
- 800 mm deep DSZ enclosures come with 10U deep roof aperture, flexible covering with 2 x 4U and 1 x 2U cover plates.
- 1.000 and 1.200 mm deep DS enclosures come with 12U deep roof aperture, flexible covering with 2 x 4U and 2 x 2U cover plates.
- Floor construction with 19" punching.
- Roof unit assemblies can also be fitted to floor section. Optional base required.
- Cable entry possibility via roof, floor and rear panel. Delivered with blanking plates.
- Brush strip cable entry panel for roof (DBK24800) optional available.
- Air vents for passive ventilation Fully pre-wired earthing.

- Includes M8 earthing point and earthing kit. Including assembly materials: 24 x Cage nuts, bolts and washers M6, 4 x Levelling feet.
- Wide range of available accessories (bases, fan-units, cable entry panels, fixed shelves, patch panels, cable management, PDUs, etc.).
- Enclosure is delivered fully-assembled on a disposable pallet.

Technické informace

Šířka (netto) (mm)	800,00
Výška (netto) (mm)	2.105,00
Hloubka (netto) (mm)	800,00
Hmotnost (netto) (kg)	100,60
Minimální teplota okolí (°C)	0
Maximální teplota okolí (°C)	40
Vhodné pro U	45U-2105 mm
Barva	RAL 7035 / RAL 5005 (světle šedá / modrá)

Tabulka objednacích čísel

POPIS	OBJ. ČÍSLO
Stojanový rozvaděč rozebíratelný 45U š.800mm hl.800mm Barva: RAL 7035 + RAL 5005	DSZ458080
Volitelné příslušenství	
Půlvložka s klíčem 333 včetně 1 ks zápuštění šroubu M5x16 mm z nerezové oceli V2A	DV900333S
Horní/spodní kabelová průchodka s protiprach.kartáčem, 2U	DBK24800
Stropní vent. jednotka, 2x ventilátor, termostat, 4U, šedá RAL7035, pro stojanové rack DS/DSZ a DSS	DLT44802-A
Boční panel (pár) podstavce pro rozvaděč DS, hl. 800mm	DSOT1280
Přední/zad.panel podstavce,perf.+protiprachový filtr,š.800mm Ke stojanovým rozvaděčům, barva RAL7035	DSOF1283
19" vyvaz.kovový panel,5x velké kovové oko, 1U, barva šedá	DBC14805
19" vyvaz.panel, 5xvelké tvrdé plastové oko, 1U, barva šedá	DBK14805
19" polička s perf.,hl. 450mm, šroub.,zátěž 80kg, 1U,RAL 7035	DFS14845-C
Napájecí panel PDU 19", 9x SCHUKO, 1U, kabel 3 m	IU070114-3
Napájecí panel PDU 19", 7x SCHUKO, přep.ochrana, 1.25U, 2 m 2m-connector cable, RAL7035	IU070113

Tabulka objednacích čísel

POPIS	OBJ. ČÍSLO
Volitelné příslušenství	
19" napájecí panel PDU, 9x Schuko, vypínač, 1U, 2 m, černý Hliníkový profil	Q7070114-A
19" napájecí panel PDU, 7x Schuko, přepěťová ochrana, 1U Přívodní kabel 2 m, černý, hliníková profil	Q7070113-A
Montážní sada M6 (šroub, matice, podložka - sada 50 ks)	DSSRA050
19" montážní deska perforovaná, výška 14U, ocelový plech Včetně šroubů a matic	DMP1914
LED osvětlovací jednotka do 19" nebo magnetická, černá Včetně PIR detektoru na pohyb, externí napájecí zdroj	DTLIGHT01
Switch L2 neřízený 24xRJ45 10/100/1000, 19", interní PSU, tichý 19" provedení, kovové šasi, interní PSU	QLGSW2457
19" patchpanel pro max. 24 keystone, neosazený, 1U, RAL 7035 Dvoudílná konstrukce rámu a vyvazovacího panelu, barva světle šedá	HSER0240GS