

Technický list produktu (datasheet): HDCR100532

Speed controller 1U for fan RAL9005 black



SCHRACK-Info

Speed controller 1U f. fan R9005 pack.

Operating voltage: 110 – 240 VAC, 50/ 60 Hz

Power consumption: max. 250 W

Switching capacity: max. 10 A

Alarm output: 1 changeover contact, 24 VUC/5 A

Switching range: +5 °C bis +50 °C

Colour: RAL 9005 jet black

For temperature-dependent, continuously variable speed

control of active fans. Plug & Play connection

(in conjunction with IS-1 Active fan set 230V - 7719305)

With external PTC sensor (1.5 m)

Front LC display for the parameterization,

and display of temperatures (current, min., max.).

When exceeding the setpoint temperature changes
the backlight from green to red.

When the alarm temperature is exceeded, the display flashes
red and the alarm contact (change-over contact) switches.

consisting of:

1 speed controller

1 power supply cable

1 temperature sensor 1,5m

Delivery condition: packed

Technické informace

Hmotnost (netto) (kg)	6,00
Minimální teplota okolí (°C)	-10
Maximální teplota okolí (°C)	60

POPIS	OBJ. ČÍSLO
Speed controller 1U for fan RAL9005 black	HDCR100532