

Technický list produktu (datasheet): IL900189--

Plug-in counter bar 50A for Vienna, Tyrol and Styria

Smart Meter Terminal 3pole +2N, Test overload current 80A for 1h, Power loss 3,3W at 50A over all three phases, 400VAC, 50Hz, Conductor Material Copper 2,5-16mm², flexible with crimped ferrule, Material Terminal Inserts from Silver-Plated Copper, RoHS konform, OVE R21:2019



SCHRACK-Info

- Meter Connection Terminal 3-pol+2N With TRE 50A, for EVU Czech Republic, Vienna, Tyrol and Styria
- It makes it possible to replace devices without interrupting the power supply
- Power loss 3,3W at 50A over all three phases
- 400VAC, 50Hz
- Material Terminal Inserts from Silver-Plated Copper
- OVE Zertifiziert, RoHS konform, OVE R21:2019
- Ambient Temperature max. 60°C
- Conductor Material/Type Copper 2,5-16mm², rigid, solid and stranded /flexible with crimped ferrule, insertion depth of conductor 18-22mm
- Meter pins IL900190
- Tightening torque of Conductor max. 3Nm
- Material PA6.6

Technické informace

Šířka (netto) (mm)	149,00
Výška (netto) (mm)	45,00
Hloubka (netto) (mm)	33,00
Hmotnost (netto) (kg)	0,11
EAN	9004840980264
Ztrátový výkon (W)	3,30
Minimální teplota okolí (°C)	0
Maximální teplota okolí (°C)	60
Oblast	Steiermark Videň Tirol
Příslušenství	elektroměřová lišta
Základní popis	Svorky

Tabulka objednacích čísel

POPIS	OBJ. ČÍSLO
Plug-in counter bar 50A for Vienna, Tyrol and Styria Smart Meter Terminal 3pole +2N, Test overload current 80A for 1h, Power loss 3,3W at 50A over all three phases, 400VAC, 50Hz, Conductor Material Copper 2,5-16mm ² , flexible with crimped ferrule, Material Terminal Inserts from Silver-Plated Copper, RoHS konform, OVE R21:2019	IL900189
Volitelné příslušenství	
Kolíky 6/5 44mm elměr	IL900309
Plug-in counter bar pins 63A, 44mm, PU=7 pieces	IL900190
Cover for Plug-in counter bars	IL900191