

Technický list produktu (datasheet): IL900189-A

## Plug-in counter bar 50A, PU = 64 Pieces

Smart Meter Terminal 3pole +2N, Test overload current 80A for 1h, Power loss 3,3W at 50A over all three phases, 400VAC, 50Hz, Conductor Material Copper 2,5-16mm<sup>2</sup>, flexible with crimped ferrule, Material Terminal Inserts from Silver-Plated Copper, RoHS konform, OVE R21:2019



### SCHRACK-Info

- Meter Connection Terminal 3-pol+2N With TRE 50A, for EVU Czech Republic, Vienna, Tyrol and Styria
- It makes it possible to replace devices without interrupting the power supply
- Power loss 3,3W at 50A over all three phases
- 400VAC, 50Hz
- Material Terminal Inserts from Silver-Plated Copper
- OVE Zertifiziert, RoHS konform, OVE R21:2019
- Ambient Temperature max. 60°C
- Conductor Material/Type Copper 2,5-16mm<sup>2</sup>, rigid, solid and stranded /flexible with crimped ferrule, insertion depth of conductor 18-22mm
- Meter pins IL900190
- Tightening torque of Conductor max. 3Nm
- Material PA6.6

### Technické informace

Šířka (netto) (mm)

149,00

## Technické informace - Pokračování

|                              |                              |
|------------------------------|------------------------------|
| Výška (netto) (mm)           | 45,00                        |
| Hloubka (netto) (mm)         | 33,00                        |
| Hmotnost (netto) (kg)        | 0,11                         |
| EAN                          | 9004840980271                |
| Ztrátový výkon (W)           | 3,30                         |
| Minimální teplota okolí (°C) | 0                            |
| Maximální teplota okolí (°C) | 60                           |
| Oblast                       | Steiermark<br>Vídeň<br>Tirol |
| Příslušenství                | elektroměrová lišta          |
| Základní popis               | Svorky                       |

## Tabulka objednacích čísel

| POPIS                                                                                                                                                                                                                                                                                                                                     | OBJ. ČÍSLO |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------|
| Plug-in counter bar 50A, PU = 64 Pieces<br>Smart Meter Terminal 3pole +2N, Test overload current 80A for 1h, Power loss 3,3W at 50A over all three phases, 400VAC, 50Hz, Conductor Material Copper 2,5-16mm <sup>2</sup> , flexible with crimped ferrule, Material Terminal Inserts from Silver-Plated Copper, RoHS konform, OVE R21:2019 | IL900189-A |
| <b>Volitelné příslušenství</b>                                                                                                                                                                                                                                                                                                            |            |
| Kolíky 6/5 44mm elměr                                                                                                                                                                                                                                                                                                                     | IL900309   |
| Plug-in counter bar pins 63A, 44mm, PU=7 pieces                                                                                                                                                                                                                                                                                           | IL900190   |
| Cover for Plug-in counter bars                                                                                                                                                                                                                                                                                                            | IL900191   |