


Technický list produktu (datasheet): LID13982--

Sutil Round LED vestavné 12W, 3K, 720lm, 120°, IP40, bílá €ECONOMY

complete with driver; 06 DOWNLIGHT FIX LED



Produktové informace

12W slim downlight LED, IP40, ideal for commercial applications such as offices, galleries and showrooms. Supplied with 250mA non-dimmable LED driver. Complies with standard EN60598-1 and any other specific standards.



Technické informace

Lumenů (lm)	720
Barva světla	Teple bílá
Teplota barvy (K)	3000
Index podání barev	≥80
Doba života	30.000h
Stmívatelné	Ne
Třída ochrany	II
Stupeň ochrany krytí	IP40
Druh svítidla	LED panel

Technické informace - Pokračování

Světelný zdroj součástí	ano
Počet světelných zdrojů	1
Patice	LED Platine
Úhel vyzařování (°)	120
Účinnost (lm/W)	60
Účinník	0,9
Výkon (W)	12
Ovládací zařízení	LED napáječ
Pracovní napájecí napětí (V)	220-240
Frekvence (Hz)	50/60
Instalace	Downlight
Výřez (mm)	Ø 155
Montážní hloubka (mm)	50
Barva	Bílá
Materiál	Akrylát Tlakově litý hliník Plast
Výška (mm)	22
Průměr (mm)	173
Volitelné příslušenství	LID16598--
Ø x V (mm)	173x22
VÝŘEZ v mm	Ø 155

Rozměrový výkres: Sutil Round LED vestavné 12W, 3K, 720lm, 120°, IP40, bílá



Tabulka objednacích čísel

POPIS	OBJ. ČÍSLO
Sutil Round LED vestavné 12W, 3K, 720lm, 120°, IP40, bílá complete with driver; 06 DOWNLIGHT FIX LED	LID13982
Volitelné příslušenství	
LED driver 230V 8-50W 1500mA dimmable IP20 230V; 23 DRIVERS	LID16598