

Technický list produktu (datasheet): Q7171199--

Extender HDMI A 1.3b přes Cat.5e/6 2xRJ45, nad 30m



SCHRACK-Info

The Q7171199-- uses two pieces of CAT 5e/6 HIGH SPEED cables to extend the HDTV display up to 60 meters for 1080P. It not only breaks the limitation of the HDMI cable transmission length, but also CAT 5e/6 has more flexibility and convenience in cable construction.

Specification

- Compliance with HDMI High Speed specification
- 2 HDMI Adapters for CAT 5/6 patch cable
- Automatic device configuration
- Supports 1080p with Cat 6 patch cable up to 30m
- HDTV: 480i/576i/480p/576p/720p/1080i/1080p
- Supports Dolby Digital, DTS Digital, DTS HD, Dolby True HD
- Bandwidth: 2.25 Gbit/s at 225 MHz per channel (8.16 Gbit/s total)
- Supports HDCP pass-through, LPCM
- Supports 8bit per channel (24bit all channel) deep color

Package contents

- 1 x Main unit NO. 1 Transmitter
- 1 x Main unit NO. 2 Receiver
- 1 x External Power Supply
- 1 x User Manual

Packaging Information

- Packing Dimension: 190×145×60 mm
- Packing Weight: 0.47kg
- Carton Dimension: 505×340×235mm
- Carton Quantity: 15pcs
- Carton Weight: 7.8kg

Technické informace

Délka (netto) (mm)	81,00
Šířka (netto) (mm)	45,00
Výška (netto) (mm)	25,00
Hmotnost (netto) (kg)	0,36
EAN	4260113565742
Minimální teplota okolí (°C)	5
Maximální teplota okolí (°C)	45
Produkt	Ostatní

Datová tabulka: Extender HDMI A 1.3b přes Cat.5e/6 2xRJ45, nad 30m

Signal Inputs/Output	
Input Video Signal	0.5 - 1.0 volts p-p
Input DDC Signal	5 volts p-p (TTL)
Maximum Single Link Range	1920x1080p
Output Video	HDMI High Speed
Operating Frequency	
Vertical Frequency Range	50/60Hz
Video Amplifier Bandwidth	1.65Gbps/165MHz
Transmission distance	
CAT-6 cable	30M for 1080p
Resolutions (HDTV)	
Interlaced (50&60Hz)	480i, 576i, 1080i
Progressive (50&60Hz)	480p, 576p, 720p, 1080p
Enviromental	
Operating Temperature	0-70°C
Operating Humidity	10 to 85% RH (no condensation)
Storage Temperature	-10 to 80°C
Storage Humidity	5 to 95% RH (no condensation)
Power Requirement	
External Power Supply	5V DC, 2A
Power consumption (Max)	5W

POPIS

OBJ. ČÍSLO

Extender HDMI A 1.3b přes Cat.5e/6 2xRJ45, nad 30m

Q7171199